

Technical Data Sheet

1. Type	EA CONTACT ADHESIVE
2. Usage	For bonding laminates to table tops, decorative metal cladding in construction industries, rubber, leather, cork, polyurethane foam, fibre glass, aluminium foil, interior decoration and furniture.
3. Application	Apply by scrapper, brush or suitable roller.
4. Physical Appearance	Viscous liquid
5. Material Composition	Synthetic elastomer / Resin in organic solvents.
6. Density	0.83 gm – 0.86 gm / ml
7. Colour	Yellowish to light brown.
8. Viscosity	3000 - 4000 cps
9. Total solid	24.5 % +/- 1% w/w
10. Tack life	5 – 30 minutes depending on surface porosity.
11. Caution	The solvents in this product are highly flammable. Use only in well ventilated area. Avoid open flame, heat, spark, ignition source, hot work or static discharge.
12. Storage	Keep lid tightly closed after used and store in cool, dry and well ventilated area away from any possible heat or spark.
13. Shelf life	12 months from manufacturing date.
14. Packing available	3.6 litre can.

Effective date : 1st January 2019

The above information is given in good faith and to the best of our knowledge. We makes no warranty or guarantee of results and assume no obligation or liabilities for the use of any product mentioned herein. We expect person(s) receiving this information to exercise their independent judgement or consult with a competent professional to determine the safety and appropriateness of this material for a specific used